Americans with Disabilities Act Ramp Guidelines

Ramps are required for any change in level greater than $\frac{1}{2}$ inch.

Ramps have a maximum slope of 1:12 (4.8 degrees)

Ramps have a minimum width of 36 inches.

There must be a minimum 5 feet by 5 feet flat area at the top and bottom of the ramp for turning.

Ramps may be no longer than 30 feet horizontally between flat rest or turn platforms.

Source: https://www.access-board.gov/guidelines-and-standards/buildings-and-sites/about-the-ada-standards/guide-to-the-ada-standards

Americans with Disabilities Act Ramp Guidelines

Ramps are required for any change in level greater than $\frac{1}{2}$ inch.

Ramps have a maximum slope of 1:12 (4.8 degrees)

Ramps have a minimum width of 36 inches.

There must be a minimum 5 feet by 5 feet flat area at the top and bottom of the ramp for turning.

Ramps may be no longer than 30 feet horizontally between flat rest or turn platforms.

Source: https://www.access-board.gov/guidelines-and-standards/buildings-and-sites/about-the-ada-standards/guide-to-the-ada-standards

Americans with Disabilities Act Ramp Guidelines

Ramps are required for any change in level greater than $\frac{1}{2}$ inch.

Ramps have a maximum slope of 1:12 (4.8 degrees)

Ramps have a minimum width of 36 inches.

There must be a minimum 5 feet by 5 feet flat area at the top and bottom of the ramp for turning.

Ramps may be no longer than 30 feet horizontally between flat rest or turn platforms.

Source: https://www.access-board.gov/guidelines-and-standards/buildings-and-sites/about-the-ada-standards/guide-to-the-ada-standards